

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 :
H01S 3/13 // 3/10, H01L 33/00

A1

(11) International Publication Number: WO 99/40654

(43) International Publication Date: 12 August 1999 (12.08.99)

(21) International Application Number: PCT/SE99/00077

(22) International Filing Date: 20 January 1999 (20.01.99)

(30) Priority Data: 21 January 1998 (21.01.98) SE
9800143-1

(71) Applicant (for all designated States except US): ALTTUN AB
[SE/SE]; Isafjordsgatan 9, S-164 40 Kista (SE).

(72) Inventors; and
(75) Inventors/Applicants (for US only): BROBERG, Björn
[SE/SE]; Lokevägen 10, S-182 61 Djursholm (SE).
ANDERSSON, Lars [SE/SE]; Kristinavägen 7, S-177 56
Järfälla (SE).

(74) Agent: NORÉNS PATENTBYRÅ AB; P.O. Box 10198, S-100
55 Stockholm (SE).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR,
BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD,
GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP,
KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK,
MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU,
ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG,
ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI,
FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent
(BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE,
SN, TD, TG).


Published

With international search report.
Before the expiration of the time limit for amending the
claims and to be republished in the event of the receipt of
amendments.
In English translation (filed in Swedish).

(54) Title: METHOD OF OPTIMIZING THE OPERATION POINTS OF LASERS AND MEANS FOR CARRYING OUT THE METHOD

(57) Abstract

A method of optimising the operation point of a laser, comprising characterising the laser and controlling the different laser sections. The invention is characterized by controlling the different laser sections (1, 2, 3) by varying the current injected into respective sections; causing the laser (30) to be sensed with respect to discontinuities occurring at mode jumps in a signal from a detection device firmly connected to the laser, effecting the control of the different laser sections (1, 2, 3) by means of a control unit (31); delivering different control combinations and the signal delivered from the detection device to the control unit (31); causing the control unit to detect the mode plane of the laser (30); storing at least a part of a mode plane or several mode planes in a memory (32) belonging to the control unit (31); and causing the control unit (31) to control different laser sections (1, 2, 3) such that the laser will obtain the desired operation point.



Best Available Copy